



SPILLTECH

SpillTech
5440 McGinnis Village Place
Suite 102
Alpharetta, GA 30005
Phone: 1-800-228-3877
Fax: 1-800-872-3764
www.spilltech.com

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: Universal Sorbent Socks
CHEMICAL FAMILY: Polypropylene
MANUFACTURER'S NAME: SpillTech

Manufacturing Location:

SpillTech
Brookley Industrial Complex
1627 O'Donoghue Street
Mobile, AL 36615

Customer Service Telephone Number: 1-800-228-3877

Technical Information Telephone Number: 1-251-694-0102 ext.121

Date Prepared: April 29, 2002

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENTS</u>	<u>PERCENT</u>	<u>CAS NUMBER</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Sock Filler:				
Polypropylene	> 99.8%	9003-07-0	N/A	N/A
Surfactant	< 0.2%	N/A	N/A	N/A
Sock Casing:				
Polypropylene	>97%	9003-07-0	N/A	N/A
Aqua Ammonia	<1.2%	1336-21-6	N/A	N/A
Dimethylethanolamine	<1.2%	108-01-0	N/A	N/A

SECTION III: HAZARDS IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0
FLAMMABILITY: 1
REACTIVITY: 0

*Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

SECTION IV: FIRST AID MEASURES

EYE CONTACT: If dust in eye, flush with water for 5 minutes then contact physician.
SKIN CONTACT: If molten material comes in contact with skin, cool under ice water or a running stream of water. Do not attempt to remove molten material from the skin. Get medical attention. If not molten, then wash with soap and water.
INHALATION: Remove to fresh air. If symptoms persist, contact physician.
INGESTION: Not considered harmful

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT: 329° C (625° F)
AUTO IGNITION: 357° C (675° F)
FLAMMABLE LIMITS: N/A
FIRE EXTINGUISHING MEDIA: Water, Foam, CO2, Dry Chemical
SPECIAL FIRE FIGHTING PROCEDURES: Wear a self-contained breathing apparatus and refer to MSDS for absorbed liquids.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Refer to MSDS for absorbed liquids. Sock does not render liquids non-flammable, neutral or less-hazardous. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VI: ACCIDENTAL RELEASE MEASURES

If material is unused: sweep or vacuum product and dispose of as a non-hazardous material. If sweeping, dampen with water spray to avoid creating dust.
If used: Refer to MSDS for absorbed liquids. Sock does not render liquids non-flammable, neutral or less-hazardous.

SECTION VII: HANDLING AND STORAGE

Avoid puncturing or tearing outer material to avoid creating dust. Store in dry area. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: None required under normal conditions.
VENTILATION: None required under normal conditions.
PROTECTIVE GLOVES: None required under normal conditions.
EYE PROTECTION: Safety glasses with side shields are recommended as a good practice for industrial safety.
OTHER PROTECTIVE EQUIPMENT (SPECIFY): None Required

SECTION IX: PHYSICAL DATA

APPEARANCE AND ODOR:	Gray particles enclosed in a gray polypropylene sock & virtually odor free
SPECIFIC GRAVITY:	0.9
BOILING POINT (C):	Not Applicable
MELTING POINT (C):	>160° C (320° F)
SOLUBILITY IN WATER:	Insoluble
PERCENT VOLATILE BY VOLUME:	<0.4%
EVAPORATION RATE:	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air = 1):	N/A

SECTION X: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non Hazardous

SECTION XI: WASTE XI DISPOSAL METHOD

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous.

Always refer to the MSDS for the chemical absorbed before proceeding

SECTION XII: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: April 29, 2002

UPDATED: February 2005

PREPARED BY: SpillTech, Telephone Number: 1-800-228-3877.