



SPILLTECH

SpillTech
5440 McGinnis Village Place
Suite 102
Alpharetta, GA 30005
Phone: 1-800-228-3877
Fax: 1-800-872-3764
www.spilltech.com

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: PolyBacked Rug Matting
CHEMICAL FAMILY: Olefin

Company Profile:

SpillTech
Brookley Industrial Complex
1627 O'Donoghue Street
Mobile, AL 36615

Customer Service Telephone Number: 1-800-228-3877

Technical Information Telephone Number: 1-251-694-0102 ext.121

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENTS</u>	<u>PERCENT</u>	<u>CAS NUMBER</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Polypropylene	< 80%	9003-07-0	N/A	N/A
Olefin Coating	10-30%	9003-07-0	N/A	N/A
Pigment	< 10%	Mixture	N/A	N/A
Minor Additives	< 8%	Mixture	N/A	N/A

SECTION III: HAZARDS IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0
FLAMMABILITY: 1
REACTIVITY: 0

* Not considered a hazardous material at temperatures below melting point. Not considered a controlled substance or a carcinogen.

* Avoid mineral acids and alkalis

* Avoid Fluorine

SECTION IV: FIRST AID MEASURES

EYE CONTACT: Use eyewash, consult physician if accompanied by pain or irritation.
SKIN CONTACT: N/A
INHALATION: N/A
INGESTION: N/A

SECTION V: FIRE FIGHTING MEASURES

FLASH POINT: 340° C (645° F) (per ASTM D1929)
AUTO IGNITION: > 550° C (1022° F)
FLAMMABLE LIMITS: N/A
FIRE EXTINGUISHING MEDIA: Water, Foam, CO2, Dry Chemical
SPECIAL FIRE FIGHTING PROCEDURES: Standard procedures for Class A fires
UNUSUAL FIRE AND EXPLOSION HAZARDS: Overheated or molten material may burn slowly with dense smoke. Avoid inhalation of vapors. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VI: ACCIDENTAL RELEASE MEASURES

If material is not contaminated, return to proper package for use. If material is contaminated, please in proper container for disposal. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding
Product is fabric made from polyolefin fibers and yarn and the roll may be very heavy. Use caution in the even of spill on uneven ground. Use suitably rated lifting equipment in the event a roll needs to be moved.

SECTION VII: HANDLING AND STORAGE

Store fabrics in a warehouse equipped with sprinkler system. Avoid temperatures above 200° F. Avoid extreme humidity. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons. Polyolefin, when heated, becomes very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire. Adequate ventilation is required to remove decomposition products when temperature exceeds melting point. Avoid contact with melted product.
Store away from oxidizing materials in a cool, dry place. Do not store in direct sunlight. No special handling needed for uncontaminated product.
Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION VIII: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION: None Required
VENTILATION: None Required
PROTECTIVE GLOVES: None Required
EYE PROTECTION: Safety glasses with side shields are recommended as a good practice for industrial safety.
OTHER PROTECTIVE EQUIPMENT (SPECIFY): None Required

SECTION IX: PHYSICAL DATA

APPEARANCE AND ODOR:	Gray or black & virtually odor free
SPECIFIC GRAVITY:	0.915
BOILING POINT (C):	Not Applicable
MELTING POINT (C):	165° C (329° F)
SOLUBILITY IN WATER:	Insoluble
PERCENT VOLATILE BY VOLUME:	N/A
EVAPORATION RATE:	N/A
VAPOR PRESSURE (mm Hg):	N/A
VAPOR DENSITY (Air = 1):	N/A

SECTION X: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non Hazardous

SECTION XI: WASTE XI DISPOSAL METHOD

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MSDS for the chemical absorbed before proceeding

SECTION XII: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: April 29, 2002

REVIEWED (no changes): February 2014

PREPARED BY: SpillTech, Telephone Number: 1-800-228-3877.